

[illegible]

Technical drawing of a stepped profile (Figure 1.10). The drawing shows a profile with a total width of 120^{+6}_{-6} mm. The profile has a vertical section on the left with a height of 45^{+3}_{-3} mm. The horizontal section has a width of 30 mm. The vertical section has a width of 5 mm. The horizontal section has a width of 85 mm. The profile is drawn on a grid.

Technical drawing of a mechanical part showing dimensions:

- Vertical Dimensions (Left Side):**
 - Total height: 70^{+1}_{-1}
 - Segment 1: $7^{+0.76}_{-0}$
 - Segment 2: 31
 - Segment 3: 13
 - Segment 4: 1^{+0}_{-0}
- Horizontal Dimensions (Bottom):**
 - Segment 1: 41^{+35}_{-0}
 - Segment 2: 10
 - Segment 3: 6^{+85}_{-0}
 - Segment 4: 61^8
 - Total width: 120^{+6}_{-6}
- Geometric Features:**
 - Four fillets labeled $R10$.
 - Two angles labeled 4° and 15° .

Grundriss, 1:10

The diagram is a circular floor plan with concentric circles and radial lines. The outermost circle has a diameter of 1240. The next circle inward has a diameter of 1000. The innermost circle has a diameter of 600. The distance between the outermost and the next circle is 120. The distance between the next circle and the innermost circle is 200. The distance between the innermost circle and the center is 300. The center is marked with a crosshair. The plan is divided into 12 radial sections by lines at 30-degree intervals. The outermost circle is labeled with a diameter of 1240. The next circle inward is labeled with a diameter of 1000. The innermost circle is labeled with a diameter of 600. The distance between the outermost and the next circle is 120. The distance between the next circle and the innermost circle is 200. The distance between the innermost circle and the center is 300. The center is marked with a crosshair. The plan is divided into 12 radial sections by lines at 30-degree intervals. The outermost circle is labeled with a diameter of 1240. The next circle inward is labeled with a diameter of 1000. The innermost circle is labeled with a diameter of 600. The distance between the outermost and the next circle is 120. The distance between the next circle and the innermost circle is 200. The distance between the innermost circle and the center is 300. The center is marked with a crosshair. The plan is divided into 12 radial sections by lines at 30-degree intervals.

Diese Zeichnung ist geistiges Eigentum des HW und darf ohne deren Einwilligung weder kopiert, vervielfältigt, weitergegeben, noch zur Ausführung benutzt werden. Art. 5 des Bundesgesetzes gegen den unlauteren Wettbewerb (UWG).